



FP collection

Stofkaart

Beetle, Bombom, Canova, Mali, Pure loop mono,
Pure loop mini, Relief, Sicla, Tondina fat, Woodstock

Meubels met een glimlach

G Divina 3

kvadrat

Designer: Finn Sködt
Composition: 100% Wool
Height: 150 cm
Selvedge: $\updownarrow$
Weight: 840 g/mtl
Light resistance: 5-7 (ISO 105-B02)

Abrasion: 45000 Martindale
Colour: there may be slight differences.
The light colours may contain dark fibres.
The environment: Nature fibres / renewable resource

Fireproof test
AS/NZS 1530.3
BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2

EN 13501, C-s1, d0, glued
IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175, 11M
US Cal. Tech. Bull. 117



DV106




DV171




DV173



DV191



DV236



DV356



DV426



DV542



DV623



DV676



DV684



DV696



DV886



DV893



DV936

G **Divina Melange 3**

kvadrat

Designer: Finn Sködt
Composition: 100% Wool
Height: 150 cm
Selvedge: †
Weight: 840 g/mtl
Light resistance: 5-7 (ISO 105-B02)

Abrasion: 45000 Martindale
Colour: there may be slight differences.
The environment: Nature fibres / renewable resource
Fireproof test
AS/NZS 1530.3

BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2
EN 13501, C-s1, d0, glued
IMO A.652(16)
NF D 60 013


NFPA 260
UNI 9175, 11M
US Cal. Tech. Bull. 117




DM120




DM180



DM260



DM427



DM471



DM547



DM571



DM647



DM731



DM871

E Field 2**kvadrat**


Designer: Alfredo Häberli
Composition: 100% Trevira
CS
Height: 140 cm
Selvedge:
Weight: 430 g/mtl

Light resistance: 6-7
(ISO 1-8)
Abrasion: 100.000
Martindale
Colour: there may be slight
differences

The environment:
reduced environmental
impact
Fireproof test
BS 5852 Crib 5
BS 5852 part 1, ig. s. 0
DIN 4102 B1

EN 1021-1/2
FAR 25.853
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
ÖNORM B1/ Q1

SN 198 898 5.2
UNI 9175 1IM
UNI 9177 Classe 1
US Cal. Bull. 117-2013

**FD123****FD132****FD142****FD173****FD182****FD192****FD222****FD233****FD242****FD343****FD373****FD443****FD463****FD623****FD643****FD662****FD663****FD673****FD693****FD723****FD733****FD763****FD773****FD782****FD793****FD843****FD933****FD943****FD963****FD983**

G **Fiord**

Designer: Louise Sigvardt & Tone Barnung
Composition: 92% Wool, 8% nylon
Width: 140 cm
Selvedge: 1
Weight: 500 g/mtl


Light resistance: 5-7 (ISO 105-B02)
Abrasion: 60000 Martindale
Colour: there may be slight differences.
The environment: Nature fibres / renewable resource

Fireproof test
BS 5852 Crib 5 with treatment
BS 5852 part 1
DIN 4102 B2
EN 1021-1/2
IMO FTP Code 2010 Part 8

NF D 60 013
UNI 9175 1IM
US Cal. Bull. 117-2013
AS/NZS 3837, class 2



FO101



FO171



FO191



FO271



FO451



FO521



FO581




FO751



FO771



FO791



FO991

Designer: Raf Simons &
Fanny Aronsen
Composizione: 100% Cotone
Larghezza: 140 cm
Cimosa: ¹/₂
Peso: 520 g/mtl
EN 13501, C-s1, d0, glued

IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175, 1IM
US Cal. Tech. Bull. 117
Resistenza alla luce: 5-6
(ISO 105-B02)

Abrasione: 100000
Martindale
Colore: possono riscontrarsi
lievi differenze
L'ambiente: Fibre naturali /
risorsa rinnovabile
Fireproof test

AS/NZS 1530.3
BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2



HA432



HA512




HA343




HA182



HA952



HA133



HA212



HA283



HA982



HA582

C Reflect

kvadrat

Designer: Patricia Urquiola
Composition: 100% poliestre riciclat
Height: 140 cm
Selvedge: ↔
Weight: 430 g
Light resistance: 6-7

(ISO 1-8)
Abrasion: 100.000
Martindale
Colour: there may be slight differences.
Fireproof test
AS/NZS 3837

class 1, ASTM E84 Class A
ASTM E84 Class B incollato
BS 5852 crib 5 con
trattamento ignifugo, BS
5852 part 1 con trattamento
ignifugo, EN1021-1/2, US Cal.
Bull.117-2013


RF104

RF154

RF164

RF174

RF184




RF194


RF204



RF224

RF274

RF374

RF404

RF444

RF464

RF564

RF574

RF614

RF644

RF674

RF694

RF714

RF774

RF794

RF824

RF884

RF944

RF984

RF994

D Revive 1

kvadrat

Designer: Georgina Wright
Composition: 100% Recycl.
polyester FR
Height: 140 cm
Selvedge:
Weight: 420 g/lin.m

Light resistance: 5-7
(ISO 1-8)
Abrasion: 80.000 Martindale
Colour: there may be slight
differences
The enviroment: reduced

environmental impact
Fireproof test
BS 5852 part 1, ig. s. 0
DIN 4102 B1
EN 1021-1/2
IMO FTP Code 2010 Part 8

NF D 60 013 with treatment
UNI 9175 1IM
US Cal. Bull. 117-2013
ÖNORM B1/ Q1



RV424




RV534




RV634



RV664



RV524



RV434




RV414



RV454



RV274




RV384




RV184



RV774




RV764



RV754



RV834




RV944




RV914




RV974




RV284




RV324




RV224



RV144



RV154



RV164



RV194

F Steelcut Trio 3

kvadrat




Designer: Dijkemeijer & Ridolfo
Composition: 90% Wool, 10% Nylon
Height: 140 cm
Selvedge:
Weight: Umami 770 g/lin.m



Light resistance: 6-7 (ISO 1-8)
NF D 60 013
NFPA 260
SN 198 898 5.5 with FR treatment
UNI 9175 1IM

US Cal. Bull. 117-2013
ÖNORM B1/Q1
Abrasion: Umami 100.000
Martindale
Colour: there may be slight differences
The environment: natural

fibres / renewable resource
Fireproof test
AS/NZS 3837, class 2
BS 5852 Crib 5 with treatment
BS 5852 part 1
DIN 4102 B1

EN 1021-1/2
IMO FTP Code 2010 Part 8




SC446

SC453

SC436

SC576

SC666

SC526

SC506




SC226

SC246

SC113

SC153

SC796

SC195

SC983

SC716

SC806

SC976

SC176

SC906

SC105


E Oceanic



camira

Composition: 100% post-consumer recycled polyester, including 50% SEQUAL yarn
Weight per square meter:







497 g/m2 ±5% Heavy duty / 10 year guarantee.
Independently certified to ≥100,000 Martindale cycles



Fastness to Rubbing: Wet: 4, Dry: 4 (ISO 105 - X12)
Flammability: EN 1021 - 1&2
Cigarette & Match
BS 7176 Low Hazard


OC01

OC02

OC03

OC04

OC05

OC06

OC07

OC08

OC10

OC11

OC12

OC13

OC14

OC15

OC16

OC09


C Patina

Designer: Finn Sködt
Composition: 69% Wool,
22% Flax, 8% Polyamide,
1% Viscose
Width: 140 cm
Selvedge: 1
Weight: 330 g/mtl


Fireproof test
EN 1021 - 1
EN 1021 - 2
BS 7176 Low Hazard
BS 5852 Ignition Source 5
BS 7176 Medium Hazard
ÖNORM B 3825 & A 3800-1

UNI 9175 Classe 1 IM
BS 5867-2: Type B
Light resistance: 5 (ISO
105-B02)
Abrasion: 100000
Martindale
Colour: there may be slight


differences.
The light colours may
contain dark fibres.
The environment: Certified
to the EU Ecolabel




PT25




PT26




PT09




PT15




PT27




PT36




PT18




PT42




PT14



PT40



PT22



PT29



PT19




PT17



PT35



PT23




PT31



PT01



PT32



PT28




PT39




PT21



PT38




PT37



PT41



PT05



PT06




PT07



PT08



PT33



PT30



PT10




PT43




PT13



PT11




PT16



PT02




PT12



PT34



PT04



PT24



PT03



PT20

E Yoredale

camira

Composition: 95% Wool, 3% Polyester, 2% Polyamide
Total width: 138 cm minimum
Weight per linear meter: 700 g/m2 ±5%
("Martindale") Abrasion

resistance. Heavy duty / 10 year guarantee. Independently certified to ≥50,000 Martindale cycles

Flammability
EN 1021 - 1&2 Cigarette & Match
BS 7176 Low Hazard
ONORM B 3825 & A 3800-1 (58kg/m3 CMHR Foam)

UNI 9175 Classe 1 IM
BS 5852 Ignition Source 5 when FR treated BS 7176
Medium Hazard when FR treated



YR01



YR02




YR03



YR04



YR12



YR14



YR15



YR16



YR17



YR18



YR20



YR25

B Miami

PinTail®

Composition: 88% Polyester, 12% Polyethylene
Total width: 140 cm (UNI EN 1773)
Weight per square

meter: 260 g/m² (± 4%) (UNI 5114)
("Martindale") Abrasion resistance: Rubs: 80000


Light resistance: 7 (ISO 105-B02)
Pilling resistance: 5 (ISO 12945-2)



ON REQUEST




WATER-REPELLENT



PM1102




PM2009




PM3560




PM1986




PM3001




PM11-3006



PM11-5010



PM5011



PM10-5018




PM11-5004



PM5001




PM7746



PM10-6025




PM11-6007




PM13-6003



PM1000



PM11-8008



PM6003



PM0000



PM11-7004



PM0978

G B-chew Trio

abitex

Composition: 98% recycled polyester, 2% elastan Lycra
Total width: ± 140 cm
Weight per square

± 850 g/m².
Dyeing: yarn dyed product.
Roll length: approx. 20 km, can also be cut-to-length at an extra cost.

measuring the roll manually and with the cutting machine can give a difference up to 5%.
Abrasion resistance: > 350.000 rubs, ISO

12947-2.
color fastness to light: 6/7-7, ISO 105 B02.
Color fastness to light:

6/7-7, ISO 105 B02.
fastness to rubbing dry 4/5, wet 4/5, ISO 105 X12.



BC103



BC104



BC106



BC107




BC305



BC307



BC605



BC703



BC705



BC803



BC807

c Step

Gabriel®

Composition: 100% Trevira
Total width: 140 cm
Width: 140 cm
Abrasion: rubs martindale
(EN ISO 12947-2)
100,000 double rubs

wyzenbeek (ASTM D4157-
07) (heavy duty upholstery)
100,000
Pilling: scale 1-5, max. 5 - EN
ISO 12945-2
Light fastness: scale 1-8,

max. 8 - EN ISO 105 B02
Rubbing fastness: scale
1-5, max. 5 - EN ISO 105x12
(wet/dry) 4-5/4-5
Maintenance: wash or dry
cleaning P(W).

Step is made of Trevira CS
which is a polyester material
suited for environments with
special requirements for
cleaning.


ST60011

ST60021

ST60091

ST60999

ST61149

ST62057

ST63075

ST64013

ST64159

ST64178

ST65011

ST65047

ST66148

ST67004

ST68118

ST68121

ST68159

ST68161

ST68163

ST68164

C Step Melange

Gabriel®

Composition: 100% Trevira
Total width: 140 cm
Width: 140 cm
Rubs martindale:(EN ISO 12947-2)100,000
double rubs wyzenbeek (ASTM

D4157-07) (heavy duty upholstery)
100,000
Pilling scale 1-5, max. 5 - EN ISO 12945-2 4-5
Light fastness: scale 1-8, max. 8 - EN ISO 105-B02 5-7

Rubbing fastness: scale
1-5, max. 5 - EN ISO 105x12 (wet/dry)
4-5/4-5
Maintenance wash or dry cleaning P(W).
Step Melange is made of Trevira

CS which is a polyester material suited for environments with special requirements for cleaning.



SM60004



SM60021



SM60092



SM61103




SM61149



SM61150




SM61151



SM61152



SM62057



SM64159



SM64178



SM64179



SM64181




SM65011



SM65047



SM66018



SM67004



SM68119



SM68158



SM68165

A Byte

AURIM®
TEXTILE ATTITUDE.

Composition 100%PL
Total width: 140 cm (UNI EN 1773)
Weight per linear meter: 460 g/LM (± 4%)
("Martindale") Abrasion resistance. Rubs: 30.000
End point (ISO 12947- 2)
Pilling resistance: 4/5 (ISO 12945-2)

Tensile strength: Length 1000 - Width 1300 (ISO 13934-1)
Seam slippage at less than 6 mm: Length >200 - Width >200 (ISO 13936-1)
Colour fastness rubbing (dry): staining CO 4/5 (ISO 105-X12)
Colour fastness rubbing

(wet): staining CO 4/5 (ISO 105-X12)
Colour fastness artificial light: 3/4 (ISO 105 B02)




No-shrink
water-repellent




BY804



BY307




BY303



BY003



BY707



BY700



BY100



BY400



BY605



BY401



BY600



BY402



BY403



BY405



BY602

A Flash No-Shrink

Composition: 100% PP
 Total width: 140 cm (UNI
 EN 1773)
 Weight per linear meter: 450
 g/LM ($\pm 4\%$)
 Weight per square meter:

320 g/m2 ($\pm 4\%$) (UNI 5114)
 ("Martindale") Abrasion
 resistance. Rubs: 70000
 End point (ISO 12947- 2)
 Pilling resistance: 5 (ISO
 12945-2)

Tensile strength: Length
 1398,87 - Width 1091,41 (ISO
 13934-1)
 Maximum elongation:
 Length 48,23% - 26,33%
 Width (ISO 13934-1)


Seam slippage (6 mm):
 Length >200 - Width >200
 (ISO 13936-1)
 Colour fastness rubbing
 (dry): staining CO 4/5 (ISO
 105-X12)

Colour fastness rubbing
 (wet): staining CO 4/5 (ISO
 105-X12)
 Colour fastness artificial
 light. Colour change: light
 5, medium 4, dark 5 (ISO


105 B02)



No-shrink




FL501



FL500




FL301




FL305




FL300




FL310




FL900




FL001



FL005




FL003




FL004




FL002




FL705



FL700




FL707




FL710




FL810



FL804



FL800



FL807




FL111



FL400




FL101




FL100



FL402




FL408



FL600



FL601



FL409



FL403



FL407



FL602







FL405



FL200

H Pelle fiore

PR
Red

PC
Cuoio

PB
Ivory

PW
Bianco

PT
Dove grey

PTM
Dark brown




PN
Nero

B Eco pelle


Composition: 76%PVC - 2%PU - 22%PES
Width: 140 cm
Weight: g/m2 540 +/-10
Cycles (ISO 5470-2): 60000
Colour fastness to dry rubbing (ISO 105-X12): 4/5
Colour fastness to wet rubbing (ISO 105-X12): 4/5
Colour fastness to light (Xenotest - blu scale) (ISO 105-B02): 6


Adhesion (ISO 2411): > 40
Tensile strenght (UNI EN ISO 1421): 600 long.
Tensile strenght (UNI EN ISO 1421): 310 trasv.
Elongation at break % (UNI EN ISO 1421): 57 long.
Elongation at break % (UNI EN ISO 1421): 120 trasv.
Tear strenght (UNI EN ISO 4674): 50 long.
Tear strenght (UNI EN ISO 4674): 50 trasv.

Cycles (UNI 4818-13): 100000
Fireproof test: EN 1021-2:2006 / UNI 9175 classe 1 IM /
BS5852-1:1979 part I - TB 117:2013


SE1007

SE1008

SE1009

SE1019



SE1020

SE1010





SE1022

SE1014

SE1021

SE1013


SE1011

SE1012

SE1023

SE1006

SE1005

SE1018

SE1003

SE1004

SE1002

SE1001

SE1015

SE1024

SE1016

SE1017
Feltro

100% Wool


F009

F008

F015

F003

F011
PARKHAUSE



CS02
Mole



CS04
Medium grey



CS06
Nusa Beige



CS07
Argil



CS09
Midnight



CS11
Dhiggiri



CS14
Yellow



CS15
Grain



CS20
Cagla



CS22
Tibetan red