



FP collection

Stofkaart

Beetle, Bombom, Canova, Mali, Pure loop mono,
Pure loop mini, Relief, Sicla, Tondina fat

Meubels met een glimlach

G Divina 3

Stof geschikt voor: Beetle, Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat



kvadrat

Designer: Finn Sködt
Composition: 100% Wool
Height: 150 cm
Selvedge: 1
Weight: 840 g/mtl
Light resistance: 5-7 (ISO 105-B02)

Abrasion: 45000 Martindale
Colour: there may be slight differences.
The light colours may contain dark fibres.
The environment: Nature fibres / renewable resource

Fireproof test
AS/NZS 1530.3
BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2

EN 13501, C-s1, d0, glued
IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175, 11M
US Cal. Tech. Bull. 117

**DV106****DV171****DV173****DV191****DV236****DV356****DV426****DV542****DV623****DV676****DV684****DV696****DV886****DV893****DV936**

G **Divina Melange 3**

Stof geschikt voor: Beetle, Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

kvadrat

Designer: Finn Sködt
Composition: 100% Wool
Height: 150 cm
Selvedge: $\updownarrow$
Weight: 840 g/mtl
Light resistance: 5-7 (ISO 105-B02)


Abrasion: 45000 Martindale
Colour: there may be slight differences.
The environment: Naturele fibres / renewable resource
Fireproof test AS/NZS 1530.3

BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2
EN 13501, C-s1, d0, glued
IMO A.652(16)
NF D 60 013


NFPA 260
UNI 9175, 11M
US Cal. Tech. Bull. 117




DM120




DM180



DM260



DM427



DM471



DM547



DM571



DM647



DM731



DM871

E Field 2

Stof geschikt voor: Canova, Sicla, Tondina fat

kvadrat



Designer: Alfredo Häberli
Composition: 100% Trevira
CS
Height: 140 cm
Selvedge:
Weight: 430 g/mtl

Light resistance: 6-7
(ISO 1-8)
Abrasion: 100.000
Martindale
Colour: there may be slight
differences

The environment:
reduced environmental
impact
Fireproof test
BS 5852 Crib 5
BS 5852 part 1, ig. s. 0
DIN 4102 B1

EN 1021-1/2
FAR 25.853
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
ÖNORM B1/ Q1

SN 198 898 5.2
UNI 9175 1IM
UNI 9177 Classe 1
US Cal. Bull. 117-2013

**FD123****FD132****FD142****FD173****FD182****FD192****FD222****FD233****FD242****FD343****FD373****FD443****FD463****FD623****FD643****FD662****FD663****FD673****FD693****FD723****FD733****FD763****FD773****FD782****FD793****FD843****FD933****FD943****FD963****FD983**

G **Fiord**

Stof geschikt voor: Beetle, Bombom, Canova, Mali, Pure loop mono/mini
Relief, Sicla, Tondina fat

kvadrat

Designer: Louise Sigvardt &
Tone Barnung
Composition: 92% Wool,
8% nylon
Width: 140 cm
Selvedge: 1
Weight: 500 g/mtl


Light resistance: 5-7 (ISO
105-B02)
Abrasion: 60000 Martindale
Colour: there may be slight
differences.
The environment: Naturele
fibres / renewable resource

Fireproof test
BS 5852 Crib 5 with
treatment
BS 5852 part 1
DIN 4102 B2
EN 1021-1/2
IMO FTP Code 2010 Part 8

NF D 60 013
UNI 9175 1IM
US Cal. Bull. 117-2013
AS/NZS 3837, class 2



FO101



FO171



FO191



FO271



FO451



FO521



FO581




FO751



FO771



FO791



FO991

G Harald 3

Stof geschikt voor: Beetle, Canova, Pure loop mono/mini,
Relief, Sicla, Tondina fat

kvadrat

Designer: Raf Simons &
Fanny Aronsen
Composizione: 100% Cotone
Larghezza: 140 cm
Cimossa: 1
Peso: 520 g/mtl
EN 13501, C-s1, d0, glued

IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175, 1IM
US Cal. Tech. Bull. 117
Resistenza alla luce: 5-6
(ISO 105-B02)

Abrasione: 100000
Martindale
Colore: possono riscontrarsi
lievi differenze
L'ambiente: Fibre naturali /
risorsa rinnovabile
Fireproof test

AS/NZS 1530.3
BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2



HA432



HA512




HA343




HA182



HA952



HA133



HA212



HA283



HA982



HA582

G Patio

Stof geschikt voor: Beetle, Bombom, Canova, Pure loop mono/mini, Relief


kvadrat

Designer: Karina Nielsen
Rios
Composition: 100% Trevira
CS
Height: 140 cm
Selvedge: ->
Weight: 560 g/lin.m

Light resistance: 7 (ISO
105-B02)
Abrasion: 50000 Martindale
Colour: there may be slight
differences.
The light colours may
contain dark fibres.

The environment: In
compliance with EU
environmental regulations
Fireproof test
BS 5852 ignition source 5
BS 5852 part 1 ignition
source 0

DIN 4102 B1, EN 1021-1/2
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
UNI 9175 1IM
US Cal. Bull. 117-2013
ÖNORM B1/Q1



PA100




PA110



PA140



PA150



PA170



PA200



PA210



PA220



PA230



PA340



PA370



PA410



PA430



PA440



PA450



PA550



PA570



PA650



PA730



PA740



PA750



PA780



PA840



PA970

G Planum

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini, Relief, Sicla, Tondina fat


kvadrat

NomePlanum - 0111
progettistaColore grezzo
genereTappetzeria Febrik
ModelloSolido
Composizione44% lana
vergine, 42% poliestere,
14% nylon

Peso700 g / lin.m
Larghezza160 cm
durabilità100.000
Martindale
Pilling4
Solidità alla luce5-6 (ISO
1-8)



PL111



PL141



PL201



PL241



PL271



PL351



PL411



PL441



PL521



PL551



PL571



PL681



PL711



PL741



PL751



PL791



PL921



PL941



PL961



PL971

C Reflect








Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

kvadrat

Designer: Patricia Urquiola
Composition: 100% poliestre
riciclati
Height: 140 cm
Selvedge: ↔
Weight: 430 g
Light resistance: 6-7

(ISO 1-8)
Abrasion: 100.000
Martindale
Colour: there may be slight
differences.
Fireproof test
AS/NZS 3837

class 1, ASTM E84 Class A
ASTM E84 Class B incollato
BS 5852 crib 5 con
trattamento ignifugo, BS
5852 part 1 con trattamento
ignifugo, EN1021-1/2, US Cal.
Bull117-2013

**RF104****RF154****RF164****RF174****RF184****RF194****RF204****RF224****RF274****RF374****RF404****RF444****RF464****RF564****RF574****RF614****RF644****RF674****RF694****RF714****RF774****RF794****RF824****RF884****RF944****RF984****RF994**

D

Revive 1

Stof geschikt voor: Bombom, Canova

kvadrat

Designer: Georgina Wright
Composition: 100% Recycl.
polyester FR
Height: 140 cm
Selvedge:
Weight: 420 g/lin.m


Light resistance: 5-7
(ISO 1-8)
Abrasion: 80.000 Martindale
Colour: there may be slight
differences
The enviroment: reduced

environmental impact
Fireproof test
BS 5852 part 1, ig. s. 0
DIN 4102 B1
EN 1021-1/2
IMO FTP Code 2010 Part 8

NF D 60 013 with treatment
UNI 9175 1IM
US Cal. Bull. 117-2013
ÖNORM B1/ Q1



RV424




RV534



RV634




RV664




RV524




RV434



RV414



RV454



RV274




RV384



RV184



RV774



RV764



RV754




RV834




RV944



RV914




RV974




RV284




RV324




RV224



RV144



RV154



RV164



RV194

F

Steelcut Trio 3

Stof geschikt voor: Bombom, Canova, Tondina fat

kvadrat











Designer: Dijkemeijer & Ridolfo
Composition: 90% Wool, 10% Nylon
Height: 140 cm
Selvedge:
Weight: Umami 770 g/lin.m

Light resistance: 6-7 (ISO 1-8)
NF D 60 013
NFPA 260
SN 198 898 5.5 with FR treatment
UNI 9175 1IM

US Cal. Bull. 117-2013
ÖNORM B1/Q1
Abrasion: Umami 100.000
Martindale
Colour: there may be slight differences
The environment: natural

fibres / renewable resource
Fireproof test
AS/NZS 3837, class 2
BS 5852 Crib 5 with treatment
BS 5852 part 1
DIN 4102 B1

EN 1021-1/2
IMO FTP Code 2010 Part 8

**SC446****SC453****SC436****SC576****SC666****SC526****SC506****SC226****SC246****SC113****SC153****SC796****SC195****SC983****SC716****SC806****SC976****SC176****SC906****SC105**

E

Oceanic







Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini, Relief, Sicla, Tondina fat

camira

Composition: 100% post-consumer recycled polyester, including 50% SEQUAL yarn
Weight per square meter:

497 g/m2 ±5% Heavy duty / 10 year guarantee.
Independently certified to ≥100,000 Martindale cycles

Fastness to Rubbing: Wet: 4, Dry: 4 (ISO 105 - X12)
Flammability: EN 1021 - 1&2
Cigarette & Match
BS 7176 Low Hazard

**OC01****OC02****OC03****OC04****OC05****OC06****OC07****OC08****OC10****OC11****OC12****OC13****OC14****OC15****OC16****OC09**

C Patina

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini, Relief, Sicla, Tondina fat


camira

Designer: Finn Sködt
Composition: 69% Wool,
22% Flax, 8% Polyamide,
1% Viscose
Width: 140 cm
Selvedge: 1
Weight: 330 g/mtl

Fireproof test
EN 1021 - 1
EN 1021 - 2
BS 7176 Low Hazard
BS 5852 Ignition Source 5
BS 7176 Medium Hazard
ÖNORM B 3825 & A 3800-1

UNI 9175 Classe 1 IM
BS 5867-2: Type B
Light resistance: 5 (ISO
105-B02)
Abrasion: 100000
Martindale
Colour: there may be slight


differences.
The light colours may
contain dark fibres.
The environment: Certified
to the EU Ecolabel



PT25



PT26



PT09



PT15




PT27



PT36



PT18




PT42



PT14



PT40



PT22



PT29



PT19



PT17



PT35



PT23




PT31



PT01




PT32



PT28



PT39




PT21




PT38



PT37



PT41



PT05



PT06




PT07



PT08



PT33



PT30




PT10



PT43




PT13



PT11



PT16



PT02



PT12



PT34



PT04



PT24



PT03



PT20

E Yoredale

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

camira

Composition: 95% Wool, 3% Polyester, 2% Polyamide
Total width: 138 cm minimum
Weight per linear meter: 700 g/m2 ±5%
("Martindale") Abrasion

resistance. Heavy duty / 10 year guarantee. Independently certified to ≥50,000 Martindale cycles

Flammability
EN 1021 - 1&2 Cigarette & Match
BS 7176 Low Hazard
ONORM B 3825 & A 3800-1 (58kg/m3 CMHR Foam)


UNI 9175 Classe 1 IM
BS 5852 Ignition Source 5 when FR treated BS 7176
Medium Hazard when FR treated




YR01



YR02



YR03



YR04



YR12



YR14



YR15



YR16



YR17



YR18



YR20



YR25

B Miami

Stof geschikt voor: Canova

PinTail®

Composition: 88%
Polyester, 12%
Polyethylene
Total width: 140 cm (UNI
EN 1773)
Weight per square

meter: 260 g/m² (± 4%)
(UNI 5114)
("Martindale") Abrasion
resistance. Rubs:
80000


Light resistance: 7 (ISO
105-B02)
Pilling resistance: 5 (ISO
12945-2)



ON REQUEST




WATER-REPELLENT



PM1102




PM2009




PM3560




PM1986




PM3001




PM11-3006



PM11-5010



PM5011



PM10-5018




PM11-5004



PM5001




PM7746



PM10-6025




PM11-6007




PM13-6003



PM1000



PM11-8008



PM6003



PM0000



PM11-7004



PM0978

G B-chew Trio

Stof geschikt voor: Canova

abitex

Composition:
98% recycled
polyester,
2% elastan Lycra
Total width: ± 140 cm.
Weight per square

± 850 g/m².
Dyeing:
yarn dyed product.
Roll length:
aprox. 20 lm, can also
be cut-to-length at an
extra cost.

measuring the roll
manually and with
the cutting machine
can give a difference
up to 5%.
Abrasion resistance:
> 350.000 rubs, ISO

12947-2.
color fastness
to light:
6/7-7, ISO 105 B02.
Color fastness
to light:

6/7-7, ISO 105 B02.
fastness to rubbing
dry 4/5, wet 4/5,
ISO 105 X12.



BC103



BC104



BC106



BC107




BC305



BC307



BC605



BC703



BC705



BC803



BC807

C Step

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

Gabriel®

Composition: 100% Trevira
Total width: 140 cm
Width: 140 cm
Abrasion: rubs martindale
(EN ISO 12947-2)
100,000 double rubs

wyzenbeek (ASTM D4157-
07) (heavy duty upholstery)
100,000
Pilling: scale 1-5, max. 5 - EN
ISO 12945-2
Light fastness: scale 1-8,

max. 8 - EN ISO 105 B02
Rubbing fastness: scale
1-5, max. 5 - EN ISO 105x12
(wet/dry) 4-5/4-5
Maintenance: wash or dry
cleaning P(W).

Step is made of Trevira CS
which is a polyester material
suited for environments with
special requirements for
cleaning.

**ST60011****ST60021****ST60091****ST60999****ST61149****ST62057****ST63075****ST64013****ST64159****ST64178****ST65011****ST65047****ST66148****ST67004****ST68118****ST68121****ST68159****ST68161****ST68163****ST68164**

C

Step Melange

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

Gabriel®

Composition: 100% Trevira
Total width: 140 cm
Width: 140 cm
Rubs martindale: (EN ISO 12947-2) 100,000
double rubs wyzenbeek (ASTM

D4157-07) (heavy duty upholstery)
100,000
Pilling scale 1-5, max. 5 - EN ISO
12945-2 4-5
Light fastness: scale 1-8, max. 8 - EN
ISO 105-B02 5-7

Rubbing fastness: scale
1-5, max. 5 - EN ISO 105x12 (wet/dry)
4-5/4-5
Maintenance wash or dry cleaning
P(W).
Step Melange is made of Trevira


CS which is a polyester material
suited for environments with special
requirements for cleaning.



SM60004




SM60021



SM60092



SM61103



SM61149




SM61150




SM61151



SM61152



SM62057



SM64159



SM64178



SM64179



SM64181




SM65011



SM65047



SM66018



SM67004



SM68119



SM68158



SM68165

A Byte

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

AURIM®
TEXTILE ATTITUDE.

Composition 100%PL
Total width: 140 cm (UNI
EN 1773)
Weight per linear meter: 460
g/LM (± 4%)
("Martindale") Abrasion
resistance. Rubs: 30.000
End point (ISO 12947- 2)
Pilling resistance: 4/5 (ISO
12945-2)

Tensile strength: Length
1000 - Width 1300 (ISO
13934-1)
Seam slippage at less than
6 mm: Length >200 - Width
>200 (ISO 13936-1)
Colour fastness rubbing
(dry): staining CO 4/5 (ISO
105-X12)
Colour fastness rubbing

(wet): staining CO 4/5 (ISO
105-X12)
Colour fastness artificial
light: 3/4 (ISO 105 B02)




No-shrink
water-repellent




BY804




BY307




BY303



BY003



BY707



BY700



BY100



BY400



BY605



BY401



BY600



BY402



BY403



BY405



BY602

A Flash No-Shrink

Stof geschikt voor: Bombom, Canova, Mali, Pure loop mono/mini,
Relief, Sicla, Tondina fat

AURIM
TEXTILE ATTITUDE.

Composition: 100% PP
Total width: 140 cm (UNI
EN 1773)
Weight per linear meter: 450
g/LM ($\pm 4\%$)
Weight per square meter:

320 g/m² ($\pm 4\%$) (UNI 5114)
("Martindale") Abrasion
resistance. Rubs: 70000
End point (ISO 12947- 2)
Pilling resistance: 5 (ISO
12945-2)

Tensile strength: Length
1398,87 - Width 1091,41 (ISO
13934-1)
Maximum elongation:
Length 48,23% - 26,33%
Width (ISO 13934-1)


Seam slippage (6 mm):
Length >200 - Width >200
(ISO 13936-1)
Colour fastness rubbing
(dry): staining CO 4/5 (ISO
105-X12)

Colour fastness rubbing
(wet): staining CO 4/5 (ISO
105-X12)
Colour fastness artificial
light. Colour change: light
5, medium 4, dark 5 (ISO


105 B02)



No-shrink




FL501



FL500




FL301




FL305




FL300




FL310




FL900




FL001



FL005




FL003




FL004




FL002




FL705



FL700




FL707




FL710




FL810



FL804




FL800



FL807



FL111




FL400



FL101




FL100



FL402




FL408




FL600




FL601




FL409




FL403




FL407



FL602



FL405



FL200

Composition: 76%PVC - 2%PU - 22%PES
Width: 140 cm
Weight: g/m2 540 +/-10
Cycles (ISO 5470-2): 60000
Colour fastness to dry rubbing (ISO 105-X12): 4/5
Colour fastness to wet rubbing (ISO 105-X12): 4/5
Colour fastness to light (Xenotest - blu scale) (ISO 105-B02): 6

Adhesion (ISO 2411): > 40
Tensile strenght (UNI EN ISO 1421): 600 long.
Tensile strenght (UNI EN ISO 1421): 310 trasv.
Elongation at break % (UNI EN ISO 1421): 57 long.
Elongation at break % (UNI EN ISO 1421): 120 trasv.
Tear strenght (UNI EN ISO 4674): 50 long.
Tear strenght (UNI EN ISO 4674): 50 trasv.

Cycles (UNI 4818-13): 100000
Fireproof test: EN 1021-2:2006 / UNI 9175 classe 1 IM /
BS5852-1:1979 part I - TB 117:2013



SE1007



SE1008



SE1009



SE1019



SE1020



SE1010



SE1022



SE1014



SE1021




SE1013



SE1011



SE1012




SE1023



SE1006




SE1005




SE1018



SE1003




SE1004




SE1002




SE1001



SE1015



SE1024



SE1016



SE1017