



FP collection

Stofkaart

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono,
Pure loop mini, Pure loop lounge, Relief, Sicla, Tondina fat, Woodstock

Meubels met een glimlach

F Canvas 2
kvadrat



Designer: Giulio Ridolfo
Composition: 90% New
wool worsted, 10% Nylon
Height: 140 cm
Selvedge: 1
Weight: 480 g/mtl




Light resistance: 6-7
(ISO 1-8)
Abrasion: 100000
Martindale
Colour: there may be slight
differences

The environment: In
compliance with EU
environmental regulations
Fireproof test
AS/NZS 1530.3
BS 5852 ig. s. 2-3


DIN 4102 B2
EN 1021-1/2
IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175 1IM

US Cal. Tech. Bull. 117
ÖNORM B1/Q1


CV414

CV446

CV546

CV424

CV454

CV576


CV644

CV674

CV364



CV694

CV684




CV794


CV746

CV734

CV836



CV926

CV974

CV996

CV936


CV964

CV264

CV764

CV854

CV244

CV224

CV614

CV716

CV216

CV114

CV124

CV134

CV154

CV174

Canvas 2 kan op de volgende modellen:

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

G **Divina 3**

Designer: Finn Sködt
Composition: 100% Wool
Height: 150 cm
Selvedge: 1
Weight: 840 g/mtl
Light resistance: 5-7 (ISO 105-B02)

Abrasion: 45000 Martindale
Colour: there may be slight differences.
The light colours may contain dark fibres.
The environment: Naturale fibres / renewable resource

Fireproof test
AS/NZS 1530.3
BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2

EN 13501, C-s1, d0, glued
IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175, 11M
US Cal. Tech. Bull. 117



DV106



DV171




DV173



DV191



DV236



DV356



DV426



DV542



DV623



DV676



DV684



DV696



DV886



DV893



DV936

Divina 3 kan op de volgende modellen:
Beetle, Flink, Loop mono, Pure loop mono/mini, Relief, Sicla, Tondina fat

Divina Melange 3

Designer: Finn Sködt
 Composition: 100% Wool
 Height: 150 cm
 Selvedge: 1
 Weight: 840 g/mtl
 Light resistance: 5-7 (ISO 105-B02)

Abrasion: 45000 Martindale
 Colour: there may be slight differences.
 The environment: Nature fibres / renewable resource
 Fireproof test
 AS/NZS 1530.3

BS 5852 ig. s. 5
 BS 5867, part 2, type B
 DIN 4102 B2, ÖNORM B1/Q1
 EN 1021-1/2
 EN 13501, C-s1, d0, glued
 IMO A.652(16)
 NF D 60 013

NFPA 260
 UNI 9175, 11M
 US Cal. Tech. Bull. 117



DM120




DM180



DM260



DM427



DM471



DM547



DM571



DM647



DM731



DM871

Divina Melange 3 kan op de volgende modellen:

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

E **Field 2****kvadrat**

Designer: Alfredo Häberli
Composition: 100% Trevira
CS
Height: 140 cm
Selvedge:
Weight: 430 g/mtl

Light resistance: 6-7
(ISO 1-8)
Abrasion: 100.000
Martindale
Colour: there may be slight
differences

The environment:
reduced environmental
impact
Fireproof test
BS 5852 Crib 5
BS 5852 part 1, ig. s. 0
DIN 4102 B1

EN 1021-1/2
FAR 25.853
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
ÖNORM B1/ Q1

SN 198 898 5.2
UNI 9175 1IM
UNI 9177 Classe 1
US Cal. Bull. 117-2013

**FD132****FD142****FD182****FD192****FD222****FD233****FD242****FD343****FD373****FD443****FD463****FD623****FD643****FD662****FD663****FD723****FD733****FD773****FD782****FD843****FD943****FD963**

Field 2 kan op de volgende modellen:

Beetle, Canova, Flink, Loop mono, Pure loop mono/mini, Relief, Sicla, Tondina fat

G **Fiord**

Designer: Louise Sigvardt & Tone Barnung
 Composition: 92% Wool, 8% nylon
 Width: 140 cm
 Selvedge: 1
 Weight: 500 g/mtl

Light resistance: 5-7 (ISO 105-B02)
 Abrasion: 60000 Martindale
 Colour: there may be slight differences.
 The environment: Nature fibres / renewable resource

Fireproof test
 BS 5852 Crib 5 with treatment
 BS 5852 part 1
 DIN 4102 B2
 EN 1021-1/2
 IMO FTP Code 2010 Part 8

NF D 60 013
 UNI 9175 1IM
 US Cal. Bull. 117-2013
 AS/NZS 3837, class 2

**FO101****FO171****FO191****FO271****FO451****FO521****FO581****FO751****FO771****FO791****FO991**

Fiord kan op de volgende modellen:

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

F Steelcut Quartet
kvadrat

Designer: Frans Dijkmeijer & Giulio Ridolfo
Composizione: 90% lana vergine, 10% nylon pettinato
Altezza: 140 cm
Cimosa:
Peso: 770 g/

Resistenza alla luce: 6-7 (ISO 1-8)
Abrasion: 100.000 Martindale
Pilling: 4-5 (ISO 1-5)
Solidità allo sfregamento: 5 (Asciutto) 4-5 (Bagnato)

ISO 105-X12
Designer: Frans Dijkmeijer & Giulio Ridolfo
Composizione: 90% new wool, worsted 10% nylon
Height: 140 cm
Selvage:

Weight: 770 g/
Light resistance: 6-7 (ISO 1-8)
Abrasion: 100.000 Martindale
Pilling: 4-5 (ISO 1-5)
Fastness to rubbing: 5 (Dry)

4-5 (Wet) ISO 105-X12
Test ignifugo – Fireproof
test Fire tests AS/NZS 1530.3 AS/NZS 3837 class 2


SQ0994

SQ0944

SQ0924

SQ0764

SQ0684

SQ0664

SQ0654

SQ0644

SQ0554

SQ0544

SQ0534

SQ0434

SQ0414

SQ0394

SQ0354

SQ0224

SQ0154

SQ0144

SQ0114

Steelcut Quartet kan op de volgende modellen:

Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

G Harald 3
kvadrat

Designer: Raf Simons & Fanny Aronsen
Composizione: 100% Cotone
Larghezza: 140 cm
Cimosa:
Peso: 520 g/mtl
EN 13501, C-s1, d0, glued

IMO A.652(16)
NF D 60 013
NFPA 260
UNI 9175, 11M
US Cal. Tech. Bull. 117
Resistenza alla luce: 5-6 (ISO 105-B02)

Abrasion: 100000 Martindale
Colore: possono riscontrarsi lievi differenze
L'ambiente: Fibre naturali / risorsa rinnovabile
Fireproof test

AS/NZS 1530.3
BS 5852 ig. s. 5
BS 5867, part 2, type B
DIN 4102 B2, ÖNORM B1/Q1
EN 1021-1/2


HA432

HA512

HA343

HA182

HA952

HA133

HA212

HA283

HA982

HA582

Harald 3 kan op de volgende modellen:


Canova, Flink, Pure loop lounge, Tondina fat

Designer: Karina Nielsen
Rios
Composition: 100% Trevira
CS
Height: 140 cm
Selvedge: ->
Weight: 560 g/lin.m


Light resistance: 7 (ISO
105-B02)
Abrasion: 50000 Martindale
Colour: there may be slight
differences.
The light colours may
contain dark fibres.

The environment: In
compliance with EU
environmental regulations
Fireproof test
BS 5852 ignition source 5
BS 5852 part 1 ignition
source 0

DIN 4102 B1, EN 1021-1/2
IMO FTP Code 2010 Part 8
NF D 60 013
NF P 92 507 M1
UNI 9175 1IM
US Cal. Bull. 117-2013
ÖNORM B1/Q1



PA100




PA110



PA140



PA150



PA170



PA200



PA210



PA220



PA230



PA340



PA370



PA410



PA430



PA440



PA450



PA550



PA570



PA650



PA730



PA740



PA750



PA780



PA840



PA970



Patio kan op de volgende modellen:
Canova, Flink, Pure loop lounge

C Reflect

Designer: Patricia Urquiola
 Composition: 100% poliestre
 riciclato
 Height: 140 cm
 Selvedge: ↔
 Weight: 430 g
 Light resistance: 6-7

(ISO 1-8)
 Abrasion: 100.000
 Martindale
 Colour: there may be slight
 differences.
 Fireproof test
 AS/NZS 3837

class 1, ASTM E84 Class A
 ASTM E84 Class B incollato
 BS 5852 crib 5 con
 trattamento ignifugo, BS
 5852 part 1 con trattamento
 ignifugo, EN1021-1/2, US Cal.
 Bull.117-2013

**RF104****RF154****RF164****RF174****RF184****RF194****RF204****RF224****RF274****RF404****RF444****RF464****RF564****RF574****RF614****RF644****RF694****RF714****RF774****RF944****RF994**

Reflect kan op de volgende modellen:

Bombom, Canova, Flink. Loop mono, Mali. Pure loop mono/mini/lounge, Relief, Sicla










D Revive 1**kvadrat**

Designer: Georgina Wright
Composition: 100% Recycl.
polyester FR
Height: 140 cm
Selvedge:
Weight: 420 g/lin.m

Light resistance: 5-7
(ISO 1-8)
Abrasion: 80.000 Martindale
Colour: there may be slight
differences
The environment: reduced

environmental impact
Fireproof test
BS 5852 part 1, ig. s. 0
DIN 4102 B1
EN 1021-1/2
IMO FTP Code 2010 Part 8

NF D 60 013 with treatment
UNI 9175 1IM
US Cal. Bull. 117-2013
ÖNORM B1/ Q1

**RV424****RV634****RV664****RV524****RV414****RV454****RV274****RV384****RV184****RV774****RV764****RV754****RV834****RV944****RV974****RV284****RV324****RV224****RV144****RV164****RV194****H Safire Safire kan op de volgende modellen: Bombom, Pure loop lounge****kvadrat**

Category:Sahco upholstery
Pattern: Solid
Composition:
43% viscose 17% polyacrylic 15%
new wool 9% cotton 8% polyester
8% linen

Width:Approx. 140 cm (Approx. 55")
Repeat:Approx. 0/0 cm (Approx.
0"/0")
Weight:1,010 g/lin. m (32.58 oz/sq ft)
Fire tests BS 5852 crib 5 with
treatment • BS 5852 part 1 • EN 1021-

1/2 • US Cal. Bull. 117-2013 • IMO FTP
Code 2010 Part 8
There are differing requirements
concerning the flame-retardancy of
textiles dependent on the area of
application, country or even region.

Our textiles pass the majority of
international standards and are also
tested for a selection of regional
requirements.ISO 105-X12

**SA0001****SA0002****SA0003****SA0004****SA0005****SA0006****SA0007****SA0008****SA0009****SA0010****SA0011****SA0012****SA0013****SA0014****SA0015****SA0016****SA0017**

E Oceanic

camira



Composition: 100% post-consumer recycled polyester, including 50% SEAQUAL yarn
Weight per square meter:

497 g/m² ±5% Heavy duty / 10 year guarantee. Independently certified to ≥100,000 Martindale cycles

Fastness to Rubbing: Wet: 4, Dry: 4 (ISO 105 - X12)
Flammability: EN 1021 - 1&2 Cigarette & Match
BS 7176 Low Hazard




OC01




OC02



OC03



OC04




OC05



OC06




OC07




OC08




OC10




OC11



OC12




OC13




OC14



OC15



OC16



OC09

Oceanic kan op de volgende modellen:

Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

E Yoredale

camira


Composition: 95% Wool, 3% Polyester, 2% Polyamide
Total width: 138 cm minimum
Weight per linear meter: 700 g/m² ±5% ("Martindale") Abrasion

resistance. Heavy duty / 10 year guarantee. Independently certified to ≥50,000 Martindale cycles

Flammability
EN 1021 - 1&2 Cigarette & Match
BS 7176 Low Hazard
ONORM B 3825 & A 3800-1 (58kg/m³ CMHR Foam)

UNI 9175 Classe 1 IM
BS 5852 Ignition Source 5 when FR treated BS 7176
Medium Hazard when FR treated




YR01



YR02



YR03



YR04



YR12



YR14



YR15



YR16



YR17



YR18



YR20



YR25

Yoredale kan op de volgende modellen:

Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat

C Norfolk

Composizione: 100% Poliestere con
trattamento antifiama Larghezza:
140 cm
Peso: 775 g/mtl
Resistenza alla luce: 6 (ISO)

105-B02)
Abrasion: 50.000 Martindale
Pilling: 4 (ISO 12945-2)
Solidità allo sfregamento: 4-5
(Asciutto) 4-5 (Bagnato) (ISO)

105-X12)
Composition: 100% Polyester with
flame retardant treatment Width:
140 cm
Weight: 775 g/mtl

Light resistance: 6 (ISO 105-B02)
Abrasion: 50.000 Martindale
Pilling: 4 (ISO 12945-2)
Fastness to rubbing: 4-5 (Dry) 4-5
(Wet) ISO 105-X12

Test ignifugo – Fireproof test
EN 1021/ 1-2
BS 5852, crib 5
NF P 92 / 503 – 507, M1
DIN 4102, B1



NF01



NF02



NF03



NF04



NF05



NF06



NF07



NF08



NF09



NF11



NF12



NF15



NF16

Norfolk kan op de volgende modellen:
Bombom, Canova, Flink, Pure loop lounge

D Rolla


Composizione: 100% Poliestere
riciclato FR
Larghezza: 148 cm
Peso: 624 g/mtl
Resistenza alla luce: 6 (ISO)

105-B02)
Abrasion: 70.000 Martindale
Pilling: 4-5 (ISO 12945-2)
Solidità allo sfregamento: 4-5
(Asciutto) 4-5 (Bagnato) (ISO)

105-X12)
Composition: 100% Recycled
polyester FR
Width: 148 cm
Weight: 624 g/mtl

Light resistance: 6 (ISO 105-B02)
Abrasion: 70.000 Martindale
Pilling: 4-5 (ISO 12945-2)
Fastness to rubbing: 4-5 (Dry) 4-5
(Wet) ISO 105-X12

Test ignifugo – Fireproof test
EN 1021/ 1-2
BS 5852, crib 5
NF D 60–013 (AM 18)
DIN 4102, B1



RL01



RL02




RL03



RL04




RL05




RL07



RL10



RL11



RL12




RL13



RL14




RL15



RL16



RL17



RL18



RL19



RL20

Rolla kan op de volgende modellen:
Bombom, Canova, Pure loop lounge

B Miami

PinTail®

Composition: 88% Polyester, 12% Polyethylene
Total width: 140 cm (UNI EN 1773)
Weight per square

meter: 260 g/m² (± 4%) (UNI 5114)
("Martindale") Abrasion resistance. Rubs: 80000

Light resistance: 7 (ISO 105-B02)
Pilling resistance: 5 (ISO 12945-2)



ON REQUEST



WATER-REPELLENT



PM1102




PM3560



PM1986



PM3001



PM11-3006



PM11-5010



PM5011



PM10-5018



PM5001



PM7746




PM10-6025



PM13-6003



PM1000



PM11-8008



PM6003



PM0000



PM0978

Miami kan op de volgende modellen: Canova, Flink

G B-chew Trio

abitex

Composition: 98% recycled polyester, 2% elastan Lycra
Total width: ± 140 cm
Weight per square

± 850 gr/m².
Dyeing: yarn dyed product.
Roll length: approx. 20 lm, can also be cut-to-length at an extra cost.

measuring the roll manually and with the cutting machine can give a difference up to 5%.
Abrasion resistance: > 350.000 rubs, ISO

12947-2.
color fastness to light: 6/7-7, ISO 105 B02.
Color fastness to light:

6/7-7, ISO 105 B02.
fastness to rubbing dry 4/5, wet 4/5, ISO 105 X12.



BC103



BC104



BC106




BC107



BC305



BC307



BC605



BC703



BC705



BC803



BC807

B-chew Trio kan op de volgende modellen: Canova, Flink

c Step Melange

Gabriel®

Composition: 100% Trevira
Total width: 140 cm
Width: 140 cm
Rubs martindale:(EN ISO 12947-2)100,000
double rubs wyzenbeek (ASTM

D4157-07) (heavy duty upholstery)
100,000
Pilling scale 1-5, max. 5 - EN ISO 12945-2 4-5
Light fastness: scale 1-8, max. 8 - EN ISO 105-B02 5-7

Rubbing fastness: scale 1-5, max. 5 - EN ISO 105x12 (wet/dry) 4-5/4-5
Maintenance wash or dry cleaning P(W).
Step Melange is made of Trevira

CS which is a polyester material suited for environments with special requirements for cleaning.



SM60004



SM60021



SM60092



SM61103



SM61149



SM61150



SM61151



SM61152



SM62057



SM64159



SM64178



SM64179



SM64181



SM65011



SM65047



SM66018



SM67004



SM68119



SM68158



SM68165

Step Melange kan op de volgende modellen:
Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

c Step

Gabriel®

Composition: 100% Trevira
Total width: 140 cm
Width: 140 cm
Abrasion: rubs martindale (EN ISO 12947-2)
100,000 double rubs

wyzenbeek (ASTM D4157-07) (heavy duty upholstery)
100,000
Pilling: scale 1-5, max. 5 - EN ISO 12945-2
Light fastness: scale 1-8,

max. 8 - EN ISO 105 B02
Rubbing fastness: scale 1-5, max. 5 - EN ISO 105x12 (wet/dry) 4-5/4-5
Maintenance: wash or dry cleaning P(W).


Step is made of Trevira CS which is a polyester material suited for environments with special requirements for cleaning.



ST60011



ST60021



ST60091



ST60999



ST61149



ST62057



ST63075



ST64013



ST64159



ST64178



ST65011



ST65047



ST66148



ST67004



ST68118



ST68121



ST68159



ST68161



ST68163



ST68164

Step kan op de volgende modellen:
Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

A Space

AURIM
TEXTILE ATTITUDE.

Composizione: 100% PPR
Altezza: 140 cm
Peso al metro quadro: 240 g/m² (± 4%) (UNI 5114)
Resistenza alla luce: 4-5 (ISO 105 B02)

Abrasion: 25.000 Martindale
Pilling: 4-5 (ISO 12945-2)
Solidità allo sfregamento: 4-5 (Asciutto) 4 (Bagnato) ISO 105-X12
Composition: 100% PPR
Height: 140 cm

Weight per square meter: 240 g/m² (± 4%) (UNI 5114)
Light resistance: 4-5 (ISO 105 B02)
Abrasion: 25.000 Martindale
Pilling: 4-5 (ISO 12945-2)
Fastness to rubbing: 4-5 (Dry) 4

(Wet) ISO 105-X12



No-shrink



SP900



SP801



SP800



SP708



SP705



SP704



SP702



SP700



SP605



SP604



SP602



SP600



SP504



SP406



SP403



SP402



SP400



SP304



SP303



SP302



SP111



SP100

Space kan op de volgende modellen:

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock

E Volta Celeste

AURIM
TEXTILE ATTITUDE.

Composizione: 100% ImNativ PL
riciclato-biodegradabile Larghezza:
140 cm
Peso: 950 g/mtl (±4%)
Resistenza alla luce: 4 (ISO 105-B02)
Abrasion: 100.000 Martindale

Pilling: 4 (ISO 12945-2)
Solidità allo sfregamento: 4-5
(Asciutto) 4-5 (Bagnato) (ISO
105-X12)
Composition: 100% Recycled-
Biodegradable imNativ PL

Width: 140 cm
Weight: 950 g/mtl (±4%)
Light resistance: 4 (ISO 105-B02)
Abrasion: 100.000 Martindale
Pilling: 4 (ISO 12945-2)
Fastness to rubbing: 4-5 (Dry) 4-5

(Wet) ISO 105-X12
Test ignifugo - Fireproof test
TB-117:2013 California Test



No-shrink



VL100



VL105



VL309



VL404



VL604



VL408



VL409



VL410



VL411



VL600



VL601



VL603



VL606



VL804



VL805



VL811



VL900

Volta Celeste kan op de volgende modellen:

Bombom, Flink

Composizione: 95%
Poliestere, 5% Cotone
Larghezza: 140 cm
Peso: 785 g/mtl (±4%)
Resistenza alla luce: 4 (ISO
105-B02)

Abrasion: 55.000
Martindale
Pilling: 4 (ISO 12945-2)
Solidità allo sfregamento:
4-5 (Asciutto) 4 (Bagnato)
(ISO 105-X12)


Composition: 95% Polyester,
5% Cotton
Width: 140 cm
Weight: 785 g/mtl (±4%)
Light resistance: 4 (ISO
105-B02)

Abrasion: 55.000 Martindale
Pilling: 4 (ISO 12945-2)
Fastness to rubbing: 4-5
(Dry) 4 (Wet) ISO 105-X12

No-shrink



NV100



NV111




NV303



NV306



NV400



NV401



NV404



NV405



NV406




NV500




NV501



NV503



NV603



NV604



NV605



NV606



NV704



NV800



NV802



NV804



NV900





NV901


Nuvole kan op de volgende modellen:

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat

H Full-grain leather

PR
Red

PC
Cuoio

PB
Ivory

PW
White

PT
Dove grey

PTM
Dark brown

PN
Nero

Full-grain leather kan op de volgende modellen:

Bombom, Flink, Loop mono, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock


B Eco Leather

Composition: 76%PVC - 2%PU - 22%PES
Width: 140 cm
Weight: g/m2 540 +/-10
Cycles (ISO 5470-2): 60000
Colour fastness to dry rubbing (ISO 105-X12): 4/5
Colour fastness to wet rubbing (ISO 105-X12): 4/5
Colour fastness to light (Xenotest - blu scale) (ISO 105-B02): 6

Adhesion (ISO 2411): > 40
Tensile strenght (UNI EN ISO 1421): 600 long.
Tensile strenght (UNI EN ISO 1421): 310 trasv.
Elongation at break % (UNI EN ISO 1421): 57 long.
Elongation at break % (UNI EN ISO 1421): 120 trasv.
Tear strenght (UNI EN ISO 4674): 50 long.
Tear strenght (UNI EN ISO 4674): 50 trasv.


Cycles (UNI 4818-13): 100000
Fireproof test: EN 1021-2:2006 / UNI 9175 classe 1 IM /
BS5852-1:1979 part 1 - TB 117:2013


SE1007

SE1008

SE1009

SE1019

SE1033

SE1035

SE1030

SE1014


SE1021

SE1031

SE1012

SE1023

SE1006

SE1018

SE1002

SE1001

SE1015

SE1024

SE1017

Eco leather kan op de volgende modellen:

Beetle, Bombom, Canova, Flink, Loop mono, Mali, Pure loop mono/mini/lounge, Relief, Sicla, Tondina fat, Woodstock